

## 高扭矩型・Z12A型/Z21型

## 免键胀套




代码	Ì	€型	国标系列	材质	表面处理		
ZEUX61	±++==	÷+17/-C=11	740491	0.450	_		
7FUX62	且性型	局扭起空	ZTZA型	S45C	无由解镀镍		











◎ 推荐安装尺寸: 轴:h8

毂:H8 ① 类似JB/T7934 Z12A型免键胀套

※ 拆卸用螺孔的螺径与锁紧螺栓相同。

型号						传递的	传递	接触面压强		DIN912-12.9级锁紧螺钉		
代码	d	D	н	H <sub>1</sub>	H <sub>2</sub>	轴向力 Ft(KN)	扭矩 Ft(Nm)	轴 N/mm²	毂 N/mm²	数量	规格	锁紧扭矩 Ts(Nm)
	25	50				, ,	799	314				
	28	55	46	40	32	64	895	281	107	6 мс	M6×35	17
	30	55					959	262			IVIO×33	17
	35	60	60			75	1306	185	83	7		
	38	65					2567	308		10	M6×50	
ZEUX61	40	0.5	62	54	44	135	2702	293	121	10	IVIO × 30	
	42	75	02			133	2837	279	121	7	M8×50	
ZEUX62	45	75					3040	260				
	48	80				154	3707	216	102	8		41
	50	80				154	3861	207	102	° '		
	55	85	72	64	56	174	4779	212	108	9	M8×55	
	60	90				193	5793	216	113	10		
	65	95				193	3276	199	107	10		


## ■Z21型


Γ							
l	代码	È	た 型	国标系列	材质	表面处理	
l	ZEUX65	直柱型	高扭矩型	Z21型	S45C		

- 特点 结构简单;
- 应用范围广泛; • 定心能力和同轴度好;
- 不能自锁;
- 传递扭矩高;
- 安装拆卸容易;
- 可根据轴的长度调节锁紧位置。
- ◎ 推荐安装尺寸:

轴:h8 毂:H8


!! 类似JB/T7934 Z21型免键胀套













型号						传递的	传递 扭矩	接触问	<b></b> 面压强	DI	N912-12.9级		重量
代码	d	D	L	L <sub>1</sub>	L2	轴向力		轴	毂	数量	规格	锁紧扭矩	里里 (kg)
1 (1)=3	u					Ft(KN)	Mt(Nm)	N/mm²	N/mm <sup>2</sup>		A7011E	Ts(Nm)	(kg)
	6	16					9	184	69				0.04
	7	17	11	10.5	13.5	3	11	155	64	3	M2.5×L10		0.01
	8	18					12	141	62				
	9	20	13	12.5	15.5	4	17	132	60	4		1	
	10	20					19	120	60		M2.5×L12		
	11	22	13	12.5			21	108	54		W2.5*L12		0.02
	12						24	102	55				
	14	26			20	6	40	94	50		M3×L16	2	0.04
	15	28	17	16.5			44	93	50				
	16	32	''		21		86	158	79		M4×L16		0.07
	17					10	88	116	56			5	0.09
	18	35		20.5	25	11	94	110	57		M4×L20		
	19		21				99	104	56				0.08
ZEUX65	20	38				17	179	169	89		M5×L20	10	0.1
	22	40			20	18	187	146	80		WI3^LZU	10	0.11
	24	47		3 25	32	24	290	155	79				0.2
	25	41				24	300	147	78	6	M6×L25		0.19
	28	50	26			34	480	186	105			17	0.22
	30	55					510	174	95				0.27
	32	55				38	600	181	105			17	0.25
	35	60		30	37	47	820	175	100	8			0.36
	38	65	31				880	157	92		M6×L30		0.43
	40	05				50	1000	171	99				0.4
	42	75		35	44	67	1410	177	99	6	M8×L35		0.67
	45	1 '3	36				1510	165	99			41	0.63
	48	80	30	35	44	86	2150	206	123	- 8			0.74
	50	00				89	2150	190	118	٥			0.7









