



直杆短型

免键胀套

代码	类型	材质	表面处理
ZEUX66	直杆短型	S45C	—
ZEUX67			无电解镀镍



拆卸用螺孔与紧固螺孔位置重叠



视角标准：第一视角

型号		D	H	P.C.D.	H ₁	H ₂	锁紧螺栓				容许最大扭矩(N·m)	容许轴向负载(KN)	重量(g)	
代码	d						M×L	个数	内六角扳手公称尺寸	紧固扭矩(N·m)				
ZEUX66 ZEUX67	20	47		34.5				8			300	29.5	240	
	22			34.5						330	230			
	24	50		37.5				9			410	33.8	250	
	25									430	240			
	28	55	26	42.5	20	18	M6×L18	10	5	12.7	530	37.8	290	
	30													
	32	60		47.5					12			730	45.4	340
	35										800	310		
	38	65		52.5					14			1010	52.9	370
	40										1060	350		
	42	75		60								1560	74.1	600
	45											1670		570
	48	80	32	65	24	21	M8×L22		6	29.4	1780		630	
	50													
	55	85		70								2530		660
	60	90		75					14			2760	91.8	700
	65	95		80					16			2990		710



请按图示订货

型号		D	H
代码	d		
ZEUX66	22	47	26
ZEUX67	24	50	

ZEUX66— d24



未税价(元)

优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

5

轴及轮孔部的推荐公差、表面粗糙度

安装面	公差	表面粗糙度
轴外径	h7(g6)	Ra1.6以下
孔轮部内径	H7	Ra3.2以下

同步轮

F3