



免键胀套

◀ 简易型 · 带定心功能

代码	类型	材质	表面处理
ZEUX21	简易型	S45C	—
ZEUX22			无电解镀镍

※拆卸用螺孔



推荐安装尺寸：

轴：h8

毂：H8

① 类似JB/T7934 Z8型免键胀套



视角标准：第一视角

※ 拆卸用螺孔的螺径与锁紧螺栓相同。

型号		D	D ₁	L ₁	L ₂	L ₃	L	传递的 轴向力	传递 扭矩	接触面压强		DIN912-12.9级锁紧螺钉		
代码	d									轴	毂	数量	规格	锁紧扭矩
								F _t (KN)	M _t (Nm)	N/mm ²	N/mm ²			
ZEUX21 ZEUX22	19								243	234				
	20	47	56					26	256	222	94	5		
	22								282	202				
	24	50	59						368	222	106			
	25						383	213						
	28	55	64	17	22	28	34	31	429	190	97	6	M6×20	17
	30									460				
	32	60	69						655	222	118			
	35							716	203					
	38	65	74					41	778	187	109	8		
	40								819	178				
	42	75	84						1361	227	127	7		
	45							65	1458	212				
	50	80	89	20	25	33	41		1620	191	119			M8×25
	55	85	94								74	2037	199	
60	90	99						2223	182	121	8			
65	95	104						83	2710	189	129	9		
70	110	119							4203	211	134			
75	115	124	24	30	40	50	120		4754	197	128	8	M10×30	83
80	120	129							4804	184	123			




请按图示订货

型号		D
代码	d	
ZEUX21	19	47
ZEUX22	20	
	22	

ZEUX21— d19



Example
使用示例



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

5